




Single stage cartridge vacuum generators mod. ECM 15S ÷ 60S

Single-stage vacuum generators, which use interchangeable-cartridge ejectors with capacities ranging from 10 to 60 NI / min. These cartridges can also be used in a parallel configuration, and after appropriate drilling may be used on the application structure thanks to their simple construction.



Art. ECM 15S ÷ 60S

Model	Working pressure															Maximum vacuum level in kPa
	3 BAR			4 BAR			5 BAR			6 BAR			7 BAR			
	vacuum level in kPa	vacuum fl ow NI/min	air consumption NI/min	vacuum level in kPa	vacuum flow NI/min	air consumption NI/min	vacuum level in kPa	vacuum flow NI/min	air consumption NI/min	vacuum level in kPa	vacuum flow NI/min	air consumption NI/min	vacuum level in kPa	vacuum flow NI/min	air consumption NI/min	
ECM 15S	67	14	21	85	15	26	87	16	31	85	16	36	83	16	41	89.0
ECM 25S	39	29	27	48	28	33	60	28	41	90	29	48	89	29	54	90.0
ECM 30S	43	27	28	58	29	35	70	30	41	84	30	48	89	31	54	88.6
ECM 35S	72	31	54	87	37	67	86	34	81	85	31	94	84	29	112	87.4
ECM 40S	51	40	55	87	42	69	89	43	83	88	43	96	87	41	113	90.0
ECM 60S	50	55	70	61	58	87	91	61	108	90	62	125	89	59	146	91.4